



Pro Series Twin Core Cable

Product Code	Power (w)	Length (mm)	Ohms (Ω)	Amps (A)	Coverage 150w/m2	Coverage 100w/m2
PS-150	150	1500	352.7	0.7	1.00	1.50
PS-200	200	2000	264.5	0.9	1.33	2.00
PS-250	250	2500	211.6	1.1	1.67	2.50
PS-300	300	3000	176.3	1.3	2.00	3.00
PS-350	350	3500	151.1	1.5	2.33	3.50
PS-400	400	4000	132.3	1.7	2.67	4.00
PS-450	450	4500	117.6	2.0	3.00	4.50
PS-500	500	5000	105.8	2.2	3.33	5.00
PS-550	550	5500	96.2	2.4	3.67	5.50
PS-600	600	6000	88.2	2.6	4.00	6.00
PS-650	650	6500	81.4	2.8	4.33	6.50
PS-700	700	7000	75.6	3.0	4.67	7.00
PS-750	750	7500	70.5	3.3	5.00	7.50
PS-800	800	8000	66.1	3.5	5.33	8.00
PS-900	900	9000	58.8	3.9	6.00	9.00
PS-1000	1000	10000	52.9	4.4	6.67	10.00
PS-1125	1125	11250	47.0	4.9	7.50	11.25
PS-1250	1250	12500	42.3	5.4	8.33	12.50
PS-1500	1500	15000	35.3	6.5	10.00	15.00
PS-1750	1750	17500	30.2	7.6	11.67	17.50
PS-2000	2000	20000	26.9	8.7	13.33	20.00
PS-2250	2250	22500	23.5	9.8	15.00	22.50
PS-2500	2500	25000	21.2	10.9	16.67	25.00
PS-2750	2750	27500	19.2	12.0	18.33	27.50
PS-3000	3000	30000	17.6	13.0	20.00	30.00

230 - 240 VAC

10W per lineal meter

2.5m Cold Tail

1.8mm x 2.77mm diameter

2.5m Cold Tail

FEP inner and outer jacket

-200 to 200 C Temperature range

2 10kOhm floor probes included